NIROL - W

(Cold - applied bitumen emulsion for waterproofing)
NIROL-W is a stable, water-soluble emulsion of bitumen, resins, mineral stabilizers

Use Nirol - W For Damp Proofing

Also Used As Prime Coat Under Waterproofing









2, El Sobki St., Dahabi Sq., Roxy, Cairo, Egypt Tel: +(202)24141003 (6Lines) Fax:+(202) 22912315 P.O.Box: 5700 Heliopolis - West, Cairo 11341















MODERN WATERPROOFING COMPANY

NIROL - W

(Cold - applied bitumen emulsion for waterproofing)

NIROL-W is a stable, water-soluble emulsion of bitumen, resins, mineral stabilizers

BITUMODENIROL

USES

Nirol-W

As a damp proof membrane for:

Concrete and masonry.

Foundation footings.

Ground beams.

Retaining walls and basements.

Priming coat for general uses.

Protective coating for concrete

ADVANTAGES

It is cold applied on horizontal or vertical surface. Has an Excellent and strong adhesion on structural

materials such as:

(Concrete, metal, wood, bricks, etc)

When it dries:

It gives a strong shining black membrane.

It is not affected by weathering conditions.

Resists attack of chlorides and sulphates

(likely to be present in ground water).

Solvent free.

Easy to apply without any heating thus economic in cost and labor.

STORAGE

Keep out of direct sunlight in covered store.