BITUMODE ALPHA

This product is certified from the Egyptian government being in compliance with the quality mark of (EOS) and ASTM D 6222- 2016



2, El Sobki St., Dahabi Sq., Roxy, Cairo, Egypt Tel: +(202)24141003 (6Lines) Fax:+(202) 22912315 P.O.Box: 5700 Heliopolis - West, Cairo 11341















MODERN WATERPROOFING COMPANY

BITUMODE ALPHA-P

APP MODIFIED BITUMEN PLASTOMERIC WATERPROOFING MEMBRANE REINFORCED WITH COMPOSITE POLYESTER.

BITUMODEALPHA

USES

BITUMODE ALPHA- P can be applied in:

Single layer roofing system for high performance requirements.

Double layer system for basement, tunnels and underground structures subject to high water pressure.

Double layer roofing system combined with BITUMODE DELTA-G fiberglass reinforced.

Toilets and wet areas inside buildings.

Retaining walls.

Under raft foundations.

Bridge deck waterproofing.

Lining of flower boxes and waterproofing of green area in roofs (for anti-root type).

ADVANTAGES

Easy to apply (by torch).

High mechanical properties.

Superb low temperature performance up to -15°C. Resistant to penetration of plant roots

(For ALPHA-P Anti-Root).

High dimensional stability. Environmentally friendly.

PRODUCT RANGE

Polyethylene Film.
Fine Sand (S).
Mineral Slated Grey (GY).
Mineral Slated Green (GRN).
Mineral Slated White (WT).
Mineral Slated Red (RD).







STORAGE

Should be stored vertically in well covered and ventilated place not subject to direct sunlight.





BITUMODE ALPHA - P

June 2023, Version